

Cellular GSM Modem for 6712 Series Samplers

This digital cellular phone modem enables Teledyne ISCO 6712 samplers (including Avalanche® and BLZZRD™ models) to transmit text message alarms to a text-enabled phone or pager. It also allows the sampler to communicate with a modem-equipped PC for remote data retrieval and control.

Remote site communication for alarms, data retrieval, and sampler control.

The modem is compatible with user-subscribed GSM digital cell phone service (such as Cingular, T-Mobile, and Vodaphone). Your GSM subscription parameters are contained on a SIM card that you install in the modem. You can change your service parameters—or provider—by replacing the SIM card.



The GSM cellular phone modem works with Isco 6712 samplers – including the Avalanche, BLZZRD Portable Refrigerated sampler shown at right. A rain gauge, 700 Series Flow Module, and/or SDI 12 multi-parameter sonde can be connected to the sampler for integrated monitoring. Data logged by the controller can be downloaded via the modem.

Optional solar power allows long-term operation in remote sites, free of dependence on utility connections.



Applications:

- Triggering sample collection remotely on command.
- Transmitting alarms to notify that samples have been collected and are awaiting retrieval.
- Remote data retrieval using Teledyne ISCO Flowlink® software.

Standard Features:

- Text-message alarms via SMS (Short Message Service) to a text-enabled phone or pager.
- Remote control of all sampler functions using a terminal program such as Hyperterminal®.
- No separate power source required—the modem receives power directly through the sampler's interrogation connection.
- Power management (via sampler programming) enables power-up during user-selected times, to extend battery life.
- Magnetic-mount external antenna.
- Activate/de-activate sampler remotely via SMS commands

Specifications

Size (HxWxD):	4.5 x 7.5 x 4.0 inches (113 x 188 x 100 mm)
Weight:	2 lbs (0.9 kg)
Enclosure:	NEMA 4X, 6 (IP67)
Power:	Provided by 6700 Series Sampler.
Operating Temperature:	0 ° to 140 °F (-20 ° to 60 °C)
Communication Speed:	9600 bps
Alarm Method:	SMS Text message (NOTE: use of SMS is required for dial-out alarms.)
Recommended Service:	Mobile terminated service is required.

Ordering Information

Description	Part Number
GSM Cellular Phone Modem for 6700 Series Samplers Includes magnetic-mount antenna with 10 ft (3m) cable.....	60-5314-563
Optional 40 watt solar power system. Will power 6712 sampler plus GSM modem and other accessories indefinitely in most remote locations.....	60-5314-347
Potted antenna in PVC housing, designed to be buried in street for manhole sampling/monitoring applications	60-5314-605
Flowlink® software	68-2540-200



The GSM modem includes a magnetic mount antenna.



Options include a 4-inch (102 mm) diameter potted antenna (below) for in-street burial at manhole installations.



Flowlink software provides data retrieval and advanced analysis. Refer to separate Flowlink brochure for complete information about this powerful data management program.

Teledyne ISCO

P.O. Box 82531, Lincoln, Nebraska, 68501 USA
Toll-free: (800) 228-4373 • Phone: (402) 464-0231 • Fax: (402) 465-3091

teledyneisco.com



Teledyne ISCO is continually improving its products and reserves the right to change product specifications, replacement parts, schematics, and instructions without notice.

